

BER SCHOOL PROJECTS  
SOUND ABSORPTION TEST OF VARIOUS PERFORATED  
MATERIALS

TE601-01F04 (REV 0) SOUND ABSORPTION LABORATORY REPORT - 5MM CIRCULAR  
PERFORATION.DOC

30 NOVEMBER 2009

Prepared for:

Martini Industries Pty Ltd

38 Aero Road

Ingleburn 2565

Attention: Mr. Malcolm McBlain



## DOCUMENT CONTROL

Date	Revision History	Non-Issued Revision	Issued Revision	Prepared By (initials)	Instructed By (initials)	Reviewed & Authorised by (initials)
30/11/2009	Prepare report	0		TW		TW

*The work presented in this document was carried out in accordance with the Renzo Tonin & Associates Quality Assurance System, which is based on Australian Standard / NZS ISO 9001.*

*This document is issued subject to review and authorisation by the Team Leader noted by the initials printed in the last column above. If no initials appear, this document shall be considered as preliminary or draft only and no reliance shall be placed upon it other than for information to be verified later.*

*This document is prepared for our Client's particular requirements which are based on a specific brief with limitations as agreed to with the Client. It is not intended for and should not be relied upon by a third party and no responsibility is undertaken to any third party without prior consent provided by Renzo Tonin & Associates. The information herein should not be reproduced, presented or reviewed except in full. Prior to passing on to a third party, the Client is to fully inform the third party of the specific brief and limitations associated with the commission.*

*The information contained herein is for the purpose of acoustics only. No claims are made and no liability is accepted in respect of design and construction issues falling outside of the specialist field of acoustics engineering including and not limited to structural integrity, fire rating, architectural buildability and fit-for-purpose, waterproofing and the like. Supplementary professional advice should be sought in respect of these issues.*

## CONTENTS

1	INTRODUCTION	4
2	REVERBERATION CHAMBER AND TEST SPECIMENS	5
	2.1 Reverberation Chamber	5
	2.2 Test Specimens Installation Method	6
	2.3 Test Specimen	6
3	RESULTS	8

### List of Tables

Table 1 – Reverberation Time and Sound Absorption Coefficient of Test Sample (5mm round perforated fibre cement sheeting, 50mm plenum with 75mm thick Polymax Prime polyester insulation)	8
Table 2 – Practical Sound Absorption Coefficient in Octave Band Frequency	9
Table 3 – Test Conditions	9

# 1 INTRODUCTION

---


Renzo Tonin & Associates was engaged to conduct sound absorption testing of perforated plasterboard and fibre cement sheeting with polyester insulation backing. The acoustic tests were carried in the reverberation chamber of the Boral laboratory at Prospect on the 18/09/2009. This report described the test specimens, its installation methods, measurement results and calculated sound absorption coefficients in accordance to the AS ISO standard 354-2066 & ISO 9613-1. In addition the noise reduction coefficient NRC of the test sample is computed in accordance to ASTM C423-08a.

The work documented in this report was carried out in accordance with the Renzo Tonin & Associates Quality Assurance System, which is based on Australian Standard / NZS ISO 9001.

## 2 REVERBERATION CHAMBER AND TEST SPECIMENS

### 2.1 Reverberation Chamber

The Boral reverberation chamber is approximately rectangular in shape with one edge wider than the other by 1.3m. The test room has a set of two 1 x 1 m plywood diffuser panels at three corners of the room and access door/stairs on the fourth corner. Figure 1 below shows the dimensions of the chamber, locations of the fixed microphone position and sound source.



Plan View of Test Room

Notes: ① to ⑥ Measurement Microphone Position at 1.5m Above Floor

● Loud Speaker Location

Height of Test Room is 3.9m

Figure 1 - Boral Reverberation Chamber Dimensions

Test Room Volume

$$V = 211.8\text{m}^3$$

Test Room Surface Area (walls, floor and ceiling)

$$S_t = 223\text{m}^2$$

## 2.2 Test Specimens Installation Method

The perforated specimen was tested in the Boral reverberation chamber. The specimen was seated on the ledge of a 3m x 3.65m timber frame approximately on centre of the test room floor. The timber frame provided the specified 50mm cavity between the test room floor and inner surface of the specimen. 75mm thick Polymax Prime polyester insulation compressed and installed in this cavity. Edges between specimen panels and timber frame were taped with duct tape, and caulking was applied to the outer edge of the timber frame where it rests on the concrete floor.




Figure 2 – Sectional View Showing Specimen Mounting Method

Surface area of each test specimen (excluding timber frame)  $S = 10.8\text{m}^2$

Air plenum between specimen inner surface and floor  $h = 50\text{mm}$

## 2.3 Test Specimen

6mm thick fibre cement sheeting with 5mm circular perforation. 75mm thick Polymax Prime polyester insulation was compressed and fitted in the 50mm air plenum between specimen and floor. The sample consists of three panels of 1.2m x 2.4m and three of panels 1.2m x 0.6m perforated boards.



**Figure 3 – Sample 2, 5mm round perforated fibre cement sheeting installed on test room floor**

### 3 RESULTS


The measured reverberation times of the empty room ( $T_1$ ) and room with absorptive specimen installed ( $T_2$ ) is shown in Table 1 . The sound absorption coefficient,  $\alpha$ , of test specimen is calculated in accordance to AS ISO 354-2006 & ISO 9613-1 from difference in measured reverberation time. These results and its 95% Confidence Interval are also tabulated in these tables.

**Table 1 – Reverberation Time and Sound Absorption Coefficient of Test Sample (5mm round perforated fibre cement sheeting, 50mm plenum with 75mm thick Polymax Prime polyester insulation)**

Frequency Band, Hz	Average Reverberation Time of Empty Room, $T_1$	Average Reverberation Time of Room with Test Sample, $T_2$	Sound Absorption Coefficient, $\alpha$	95% Confidence Interval, $\alpha$
100	7.23	5.4	0.15	0.07
125	7.6	4.7	0.26	0.05
160	7.96	4.23	0.35	0.06
200	7.09	3.37	0.50	0.04
250	5.79	2.7	0.63	0.03
315	5.42	2.24	0.83	0.05
400	4.48	1.92	0.94	0.02
500	3.84	1.72	1.02	0.01
630	3.26	1.61	1.00	0.02
800	3.06	1.65	0.89	0.01
1000	2.85	1.65	0.81	0.01
1250	2.63	1.68	0.69	0.01
1600	2.6	1.75	0.59	0.01
2000	2.49	1.76	0.53	0.01
2500	2.31	1.66	0.54	0.01
3150	2.07	1.48	0.61	0.01
4000	1.82	1.38	0.56	0.01
5000	1.64	1.30	0.50	0.01

*Notes:*

1. Average Reverberation Time is arithmetic average of measured reverberation time inside laboratory test room
2. Sound Absorption Coefficient is calculated accordance to AS ISO 354-2006 & ISO 9613-1
3. NRC calculated in accordance ASTM C423-08a - arithmetic average of sound absorption coefficient at 100, 250, 500, 1000 & 2000Hz



**Figure 4 - Reverberation Time and Sound Absorption Coefficient of Sample 2**

The Practical Sound Absorption Coefficient of the test sample in octave band frequencies are shown in Table 2 below.

**Table 2 – Practical Sound Absorption Coefficient in Octave Band Frequency**

Frequency Band, Hz	125	250	500	1000	2000	4000
Practical Sound Absorption Coefficient, $\alpha_s$	0.25	0.65	1.00	0.80	0.55	0.55

The Noise Reduction Coefficient (**NRC**) of test sample in accordance with ASTM C423-8a is **0.75**

The atmospheric conditions of the reverberation chamber during the tests were:

**Table 3 – Test Conditions**

	Test Room Conditions		
	Empty	Sample 1 Installed	Sample 2 Installed
Air temperature	18.4 °C	18.7 °C	19.3 °C
Relative Humidity	84 %	89 %	86 %