



# Decor Systems Decorative Acoustic Panels Maintenance Procedure

## Introduction

This panels system is a highly durable modular wall and ceiling paneling system that is factory finished. Substrates include MDF, plywood and fibre cement.

## Care and Maintenance

### General Regular Cleaning

This is best carried out with a sponge or soft cloth and any household cleaning detergents. Abrasive cleaning agents must not be used.

### Polishing

The product is suitable for polishing with a soft cloth if required.

### Graffiti Removal

Pressure pack (ie. Paint) damage is usually easily removed by wiping with a mineral turpentine saturated rag within 48 hours of application. Felt tipped marker damage should be removed using methylated spirits- again, within 48 hours.

### Mechanical Damage

Should the panels be physically scored, chipped or scraped in any way please consult Décor Systems for the best method of repair / replacement. Scratch damage can usually be repaired simply by application of the top coat colour (available from the manufacturer) using a fine camel hair brush.

**DISCLAIMER:** Any advice, recommendations, information, assistance or service provided by Decor Systems in relation to goods manufactured by it or their use and application is given in good faith and believed by Decor Systems to be appropriate and reliable. Since the use and application of this product is beyond our control we cannot be held responsible for product field performance. The information presented above is the result of our considerable experience with this product but is not to be construed as a performance warranty.